Article: 9560E

Dimensions in mm 570 Backrest: Seat: H: 450-620

> B 470

Packing data 21 Weight kg

Volume m³ 0.25



bimos

Base equipment Benefit Conductivity Volume conductive plastic back rest Exceeds the requirements of ESD protection according to standard DIN EN 61340-5-1. All metal components have a conductive coating 100% ESD protection. Typical discharge resistance of 10⁶ Ohm Conductive glides. Chair element (without upholstery) The chair consists of two elements (1+1): The 1+1 system enables you to adapt this chair for The chair element with base and mechanism nearly every workplace scenario. and the upholstery element (model 9588) The upholstery element and the chair element are both Flex strip available in the colours Happy individually configurable and are freely combinable. orange, Cool grey, Mars green or Ocean blue. Simple change of the upholstery elements, resulting in sustainability, flexibility and economy. Seat and backrest Ergonomically designed, wide at the bottom Maximum liberty of action. Offers elbow-room without and narrow at the top. having to sacrifice the support of the back. Ergonomically designed seat with integrated The seat automatically encourages the correct posture and upright, healthy sitting. pelvic support and rounded front edge of the The round front edge of the seat prevents blocked seat circulation in the thighs. Sustainability, flexibility, economy, Upholster elements ("Klick-system" changeable without any tools). individuality and changeability Duotec fabric: The upholstery is breathable and assimilates and Hard-wearing, breathable and comfortable releases humidity. The particularly soft cover guarantees a maximum sitting comfort and a pleasant sitting climate. Selectable in colour black (9801), blue (9802), grey (9811). Magic artificial leather: The soft and comfortable upholstery offers a very high High-quality synthetic leather, washable, sitting comfort. However, damages caused by sharp low-maintenance and impervious to oil and parts can not be excluded. Ideal for the use in production disinfecting agents and laboratory. Selectable in colour black (MG01). Integral foam (PU): The use of integral foam is recommended for work The integral foam upholstery provides excellent environments where the chair is in contact with aggressive substances. The surface is insensitive, resistance to external influences and ease of cleaning extremely robust, washable and simple and easy to Selectable in colour black (2000). clean Very resistant against sharp objects. Supertec - an innovative fabric covering New cussion material for comfortable and robust Comfortable and soft breathable and very workplace chairs in production areas. Offers an excellent restistant to external influences. Cut resistant, sitting comfort thanks to a breathable lower tissue.

anti-slip and easy to clean.

protective cover.

Selectable in colour black (CP01).

Continuous seat height adjustment from 450 -620 mm self-supporting safety gas spring with

ESD Neon

Seat height

Resists damages caused by sharp parts through the use

The seat height adjustment can be adapted to the body

size and the height of workbenches. Wide range of

of protective studs on the surface.

height adjustment.

Volume

Article: 9560E

 Dimensions in mm
 Backrest:
 H:
 570

 Seat:
 H:
 450-620

 B:
 470

Packing data
Weight
kg
21

т³

0,25



Ergonomic package	Permanent contact backrest (-2 to 19°)	Follows the user's movements and ensures that the back remains always fully supported. The lumbar region is ideally supported in all seating positions. The backrest can be locked in 4 different positions if required.
	Weight regulation from 50 - 120 kg	Individual adjustment of the backrests and the backpressure to size and weight of the sitting person.
	Seat inclination adjustable up to 9°	Avoids a tilt-back of the hips in a bending forward position. The bigger seat angle between the thighs and the upper body additionally relieves the organism.
	Shiftable seat for individual adjustment of the seat depth (60 mm)	Matches the depth of the seat to the size of the body, giving the best possible contact surface fort he thighs.
	Backrest height adjustment easily and conveniently to operate, also in a sitting position (60 mm)	Ensures best possible support of the back - especially in the lumbar area. Adjustment possible for small and tall sized people.
	Quick adjustment	Every function can be operated easily and comfortably in a sitting position.
	Anti-shock lock	The backrest cannot accidentally spring forward even after the lock has been released.
Base	Aluminium, powder coated, black. Flat design.	Very high stability, longevity and steadiness. Flat design prevents stumbling hazard.
Glides	Wear proof plastic glides with a large surface area.	Offer a superb level of stability.
Materials	The materials used are correctly sorted and recyclable.	Environment-friendly.
Standards	EN 61340-5-1 DIN 68 877 German GS "safety tested" certificate Quality Management System DIN EN ISO 9001 Environmental Management System DIN EN ISO 14001 EMAS OHSAS EcoVadis CSR rating 2015 gold Blue Angel Eco Label Non-toxic Fraunhofer ergonomic report.	100% ESD protection Procuring is insured High level of safety and comfort High quality product.
Warranty	10 year long term warranty, 3 years full warranty.	Guaranteed quality and high efficiency.

Article: 9560E

Dimensions in mm	Backrest:	H:	570
	Seat:	H:	450-620
		B:	470
Dacking data	Waight	lea.	21
Packing data	Weight	kg	21
	Volume	m³	0,25



Article: 9560E

Dimensions in mm	Backrest:	H:	570
	Seat:	H:	450-620
		B:	470
Packing data	Weight	kg	21
	Volume	m³	0,25



Options		Benefit
Armrests (9589E)	Multifunctional armrests Height-adjustable (by 110 mm in 11 levels), Width-adjustable (by 20mm each, continuously variable), Depth-adjustable (50 mm), Swivellable (30°), Soft.	By the height adjustment of the armrests, a decompression of the neck musculature is achieved.
Options	Aluminium base, polished.	Very high stability, longevity and steadiness. Flat design prevents stumbling hazard.