

## characteristics ESD Unitec 3 with glides and footring

Article: 9651E artificial leather

Dimensions in mm	Backrest:	H:	460
	Seat:	H:	580-850
		B:	460
		T:	470
Packing data	Weight	kg	15,0
	Volume	m <sup>3</sup>	0,15



### Base equipment

### Benefit

Conductivity	The metal components have a conductive coating. The high-comfort upholstery is also conductive. Typical discharge resistance of 10 <sup>6</sup> Ohm. Conductive glides.	Exceeds the requirements of ESD protection according to standard DIN EN 61340-5-1. 100% ESD protection.
Backrest	Large, ergonomically designed backrest to take the strain off the spine and muscles with integrated lumbar support.  Backrest height adjustment convenient and easy to handle in sitting position.	Healthy posture due to a hump providing support for the back in the lumbar region.  The support area can be adapted in accordance to the user's body size.
Seat	Ergonomically designed seat with rounded front edge.	The round front edge of the seat prevents blocked circulation in the thighs.
Finishes for seat and backrest	ESD synthetic leather upholstery: High-level ESD synthetic leather Skai Tundra. Resistant to desinfectants, washable and easy-care. Colour: black (2571).	The soft and comfortable upholstery provides a comfortable feel. However, damages caused by sharp parts can not be excluded. Ideal for the use in production and laboratory.
Seat height	Stepless seat height setting from 580 - 850 mm supported by safety gas spring with protective cover.	Seat height can be adapted to nearly 95 % of all body sizes, the cover protects the gas spring from dust and dirt.
Functions / Mechanism	Permanent contact backrest  Quick adjustment	This mechanism ensures that the backrest responds immediately to any movements of the upper body by following them. Thus, the back remains supported all the time. The backrest can also be locked into any tilt position if required.  Every function can be operated comfortable and easy in sitting position.
Base	Black 5 star base made from steel shape tube, conductive, powder-coated, black. Flat design.	Very high stability, longevity. Flat design prevents stumbling hazard.
Glides	Wearproof plastic glides with a large surface area, conductive.	Offer a superb level of stability.
Foot ring	Foot ring.	The foot ring can be retrofitted by attaching it to the chair column.
Materials	The materials used are recyclable.	Environmentally friendly.
Standards	DIN EN European standard 61340-5-1 for ESD-protected areas DIN 68 877 German GS "safety tested" mark of conformity. Quality Management System DIN EN ISO 9001. Regulation EWG Nr. 1836/93. Environmental Management System DIN ISO 14001.	100% ESD protection. Procuring is insured.

**characteristics ESD Unitec 3 with glides and footing**

Article: 9651E artificial leather

Dimensions in mm	Backrest:	H:	460
		Seat:	H: 580-850
		B:	460
		T:	470

Packing data	Weight	kg	15,0
	Volume	m <sup>3</sup>	0,15

Warranty	10 year long term warranty, 3 years full warranty.
----------	--



Guaranteed quality and high efficiency.

**characteristics ESD Unitec 3 with glides and footring**

Article: 9651E artificial leather

Dimensions in mm	Backrest:	H:	460
		Seat:	H: 580-850
		B:	460
		T:	470
Packing data	Weight	kg	15,0
	Volume	m <sup>3</sup>	0,15

**Options**

Armrests

Loop armrest.

**Benefit**

Made of polyamide, adjustable in width (20 mm).